

VARACTOR DIODES

*:Dual type

V_R (V)	12	16	20	32	C2 (pF) f=1MHz	C2 (pF) f=1MHz	Package
FM			1S553T		10~18 (6V)		Plastic
AM Electronic Tuning	SVC303Y				40~600 (1V)	<35 (9V)	Plastic
	SVC321				388.1~459.1 (1.2V)	20.30~27.05 (8V)	Plastic
	SVC321SP				388.1~459.1 (1.2V)	20.30~27.05 (8V)	Plastic (SP)
		SVC311			399.7~516.8 (1V)	25.19~46.87 (9V)	Plastic
				SVC333	345.0~408.4 (3V)	18.92~25.61 (25V)	Plastic
FM Electronic Tuning	SVC201Y				39 (1V)	8.4~12.6 (9V)	Plastic
	SVC201SP				39 (1V)	8.4~12.6 (9V)	Plastic
	SVC202*				28.19~37.45 (1.6V)	10.17~12.99 (7.5V)	Plastic (NP)
	SVC251Y				23~38 (1.6V)	11~19 (5V)	Plastic
		SVC203*			36.92~43.03 (3.0V)	12.64~16.84 (8V)	Plastic
				SVC211*	37.0~42.0 (3V)	13.5~16.5 (30V)	Plastic (NP)
				SVC211SP*	37.0~42.0 (3V)	13.5~16.5 (30V)	Plastic (SP)

GERMANIUM DIODES

V_{RM} (V) I_o (mA)	15	40	c_i (pF)	(%)	I_F (mA)	I_R (μA)	Package
20	1S426		0.8	45~	2.0~	~100	Glass
50		1S188AM	0.8	50~	4.0~	~75	Glass
50		1S188FM	0.8	50~	4.0~	~23	Glass