

シリコン整流スタック・ブリッジ Bridge type

品名	I _o (A)	VRM (V)	I _{FSM} (A)	V _F (max.) (V)	I _R (max.) (μA)	外形図
SIYB10	0.4	100	30	1.05	10	2
SIYB20						
SIYB40						
SIYB60						
SIWB (A) 10	1	100	30	1.05	10	3
SIWB (A) 20						
SIWB (A) 40						
SIWB (A) 60						
SIVB10	1	100	30	1.05	10	5
SIVB20						
SIVB40						
SIVB60						
SIVB20Z	1	200	30	1.05	10	5
SIVB40Z						
SIVB60Z						
SIRBA10	1	100	30	1.05	10	6
SIRBA20						
SIRBA40						
SIRBA60						
SIRBA80						
SIRBA20Z	1	200	30	1.05	10	6
SIRBA40Z						
S2VB10	2	100	40	1.05	10	7
S2VB20						
S2VB40						
S2VB60						
S3WB10	2.3	100	120	1.05	10	8
S3WB20						
S3WB40						
S3WB60						
S4VB10	4	100	80	1.05	10	9
S4VB20						
S4VB40						
S4VB60						
D5SB10	5	100	170	1.05	10	10
D5SB20						
D5SB40						
D5SB60						
S5VB10	6	100	200	1.05	10	11
S5VB20						
S5VB40						
S5VB60						

